





## Manual Speed Control Fan



Circular type LED with switchable modes



Twister Bearing (100K hours lifetime)



Detachable fan blades design



Shining sputtering finish



Fan controller (speed and LED modes)




Isolator-mounts

## Features

- Patented circular type LED with up to 7 switchable modes
- Shining sputtering finish with glossy mirror-like surface
- Manual fan speed control for optimized fan performance
- Patented Twister Bearing technology for longer lifetime and low noise
- Detachable blades for easy cleaning
- Isolator-mount for shockproof and easy installation

## Colors



UCAPV12A-BL(blue)



UCAPV12A-R(red)



UCAPV12A-G(green)



UCAPV12A-S(silver)



UCAPV12A-GO(gold)

## Switchable LED modes



M1



ALL ON

M2




LIGHTHOUSE

M3



PROPELLER

M4




TRIPLE  
PROPELLER

M5



FLASH

M6



VEGAS  
( M2~M5 repeated )

M7



ALL OFF

## Specifications



Item	UCAPV12A	UCAPV14A
Dimension (mm)	120(W)*120(H)*25(D)	139(W)*139(H)*25(D)
Bearing Type	--- Twister Bearing ---	
Coating	--- Sputtering finish ---	
LED Number	18	18
LED Type	Circular type LED with switchable LED modes	
LED Modes	7	7
Speed (RPM)	800-2000	700-1500
Air Flow (m <sup>3</sup> /h)	56.51-143.72	71.99-154.27
Static Pressure (mm-H <sub>2</sub> O)	0.971-2.383	0.855-1.772
Minimal Noise (dBA)	16	15
MTBF (hour)	100,000	100,000
Input Power (W)	4.8	4.8
Input Current (A)	0.4	0.4
Rated Voltage (V)	12	12
Available models (color)	BL / R / G / S / GO	BL / R
Accessory	4 x Isolator-mount, 1 x fan controller, 1 x fan controller sticker	
Safety & EMC	